

DATENBLATT	5550 2470
SILVYN® MPC	gültig ab : 14.03.2011

Die SILVYN® MPC ist eine Schlauchverschraubung aus Polyamid für glatte und gewellte Kunststoffschläuche.
Der Sechskant Zwischenstutzen mit integrierter Schlauchaufnahme ermöglicht eine optimale Montage.



Maßtabelle:

Art. Nr. RAL 9005	Art. Nr. RAL 7001	PG Größe	Lichte Weite
5550 2470	5550 2496	9	8,0
5550 2471	5550 2497	11	11,0
5550 2472	5550 2498	13,5/1	11,0
5550 2494	5550 2499	13,5/2	11,0
5550 2473	5550 2451	16	14,0
5550 2474	5550 2452	21	19,0
5550 2495	5550 2453	29/1	25,0
5550 2476	5550 2454	29/2	25,0
5550 2477	5550 2455	36	33,0
5550 2478	5550 2456	48/1	48,0
5550 2479	5550 2457	48/2	48,0

Art. Nr. RAL 9005	Art. Nr. RAL 7001	PG Größe	 passend zu SILVYN® SI	 passend zu SILVYN® SP/ SP-PU	 passend zu SILVYN® EL/ELÖ/ELT
5550 2470	5550 2496	9	11 x 14		10 x 14,7
5550 2471	5550 2497	11	13 x 16	12 x 16	12 x 16,6
5550 2472	5550 2498	13,5/1	13 x 16	12 x 16	12 x 16,6
5550 2494	5550 2499	13,5/2		16 x 20	16 x 20,7
5550 2473	5550 2451	16		16 x 20	16 x 20,7
5550 2474	5550 2452	21		22 x 27	22 x 27,7
5550 2495	5550 2453	29/1			28 x 33,5
5550 2476	5550 2454	29/2			25 x 30,6
5550 2477	5550 2455	36			35 x 41
5550 2478	5550 2456	48/1			40 x 46,4
5550 2479	5550 2457	48/2			50 x 57,2



DATENBLATT	5550 2470
SILVYN® MPC	gültig ab : 14.03.2011

Material:
Grundkörper halogenfreies PA

Beständigkeit:
UV- beständig
Öl- beständig

Eigenschaften:
Staubschutz
Feuchtigkeitsschutz
Zugfest

Farbe:
schwarz
grau

Schutzart:
IP 65

Temperaturbereich:
-50°C bis +135°C

Norm Referenzen:

