

Leiteranschlussklemme, 1,5-16qmm, f. 5mm











Powering Business Worldwide™

Typ **AKU16/5**
 Art.-Nr. **107187**

Katalog Nr.

Lieferprogramm

Sortiment			60-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	7.5 x 7.5
Breite		mm	11.5
Bemessungsbetriebsstrom	I_e	A	180
Cu-Schiene		mm	1.5 - 16 mm ² AWG 14 - AWG 6.  direkt geklemmt,   8 x 6 x 0.5
verwendbar für			Alle 5 mm dicken Flachschielen
Hinweise			
○ Rundleiter eindrätig			
 Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse			
○ Rundleiter mehrdrätig			
 Sektorleiter eindrätig			
 Sektorleiter mehrdrätig			
 CU-Band			
 CU-Schiene			

Approbationen

Product Standards
 UL File No.
 UL Category Control No.
 CSA File No.
 CSA Class No.
 North America Certification
 Conditions of Acceptability
 Specially designed for North America
 Suitable for
 Current Limiting Circuit-Breaker
 Max. Voltage Rating
 Degree of Protection

UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
 E307559
 NMTR2, NMTR8
 236217
 3211-37
 UL recognized, CSA certified
 Refer to approbation report
 No
 Feeder circuits
 Refer to approbation report
 600 V AC
 Feeder circuits

Abmessungen

