



Leiteranschlussklemme, 16-70qmm, f. 5 mm











Powering Business Worldwide™

Typ **AKU70/5**
 Art.-Nr. **107189**

Katalog Nr.

Lieferprogramm

Sortiment			60-mm-System Compact-System
Grundfunktion			Anschluss- und Verbindungstechnik
Untersortiment			Universal-Leiteranschlussklemmen
Beschreibung			mit integrierter Haltefeder, geöffnetem Klemmraum und unverlierbarer Klemmschraube
Klemmraum B x H		mm	14 x 14
Breite		mm	20.5
Bemessungsbetriebsstrom	I_e	A	400
Cu-Schiene		mm	16 - 70 mm ² AWG 4 - AWG 2/0.  direkt geklemmt,   2 x (3 x 9 x 0.8) oder 6 x 9 x 0.8
verwendbar für			Alle 5 mm dicken Flachschienen
Hinweise			
○ Rundleiter eindrätig			
 Rundleiter feindrätig mit fachgerecht verpresster Aderendhülse			
● Rundleiter mehrdrätig			
 Sektorleiter eindrätig			
 Sektorleiter mehrdrätig			
 CU-Band			
 CU-Schiene			

Approbationen

Product Standards	UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.	E307559
UL Category Control No.	NMTR2, NMTR8
CSA File No.	236217
CSA Class No.	3211-37
North America Certification	UL recognized, CSA certified
Conditions of Acceptability	Refer to approbation report
Specially designed for North America	No
Suitable for	Feeder circuits
Current Limiting Circuit-Breaker	Refer to approbation report
Max. Voltage Rating	600 V AC
Degree of Protection	Feeder circuits

Abmessungen

