



Product data sheet

Item No. 92.943.0053.1

Female connector with strain relief GST18I4F B2 ZR1 SW

Connector GST18i4, 4 pole, female, spring clamp connection, for cable diameter 9,5 - 11,5 mm, 250V/16A, color of coding: black, color of housing: black



| Item No. | 92.943.0053.1 |
|------------|---------------|
| EAN | 4015573410565 |
| Order Unit | 50 Piece(s) |

Certificates / Approvals



Technical data

General Rated current 16 A Rated voltage 400 V Rated impulse voltage 4 kV Pull relief Yes Pollution degree 2 Mechanical coding Yes Interlockable Yes Color of coding/ contact carrier Black Marking of poles Color of housing inclusive strain relief Black

Connection Data

| Cable diameter | 11.5 mm |
|-----------------------------------|---------------------|
| Cable diameter 2 | 9.5 mm |
| Connection cross section solid | 2.5 mm ² |
| Cross section solid 2 | 0.75 mm² |
| Connection cross section stranded | 1.5 mm ² |
| Cross section stranded 2 | 0.75 mm² |

💎 wieland



| Terminations per pole | 2 |
|-----------------------|-------|
| Model | |
| Ma dat | Dura. |

| - L | Viodel | Bus |
|-----|------------------------------|--|
| | Number of poles | 4 |
| | Connection type | Tension clamp connection |
| | Degree of protection (IP) | IP40 |
| | Remark to type of connection | Finely stranded con. req. Wieland cable end sleeve |

Material

| Housing material | Polyamide |
|---|------------|
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continous temperature | 100 °C |
| Surface finish | Tin-plated |

Dimensions

| Length | 75 mm |
|--------|----------|
| Width | 42.25 mm |
| Height | 17 mm |

Technical drawing

