

Product data sheet

Item No. 92.934.0153.0

Male connector with strain relief GST18i3F S2 ZR1 GR01

Connector GST18i3, 3 pole, male, spring clamp connection, 250V/16A, color of coding: pebble gray, color of housing: black



Item No.	92.934.0153.0
EAN	4015573410541
Order Unit	50 Piece(s)

Certificates / Approvals



Technical data

**General**

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Pebble gray
Marking of poles	
Color of housing inclusive strain relief	Black

**Connection Data**

Cable diameter	10.3 mm
Cable diameter 2	7.8 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.5 mm <sup>2</sup>
Connection cross section stranded	1.5 mm <sup>2</sup>
Cross section stranded 2	0.5 mm <sup>2</sup>

Terminations per pole	2
-----------------------	---

**Model**

Model	Plug
Number of poles	3
Connection type	Tension clamp connection
Degree of protection (IP)	IP40
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Tin-plated

**Dimensions**

Length	75 mm
Width	32.5 mm
Height	15.5 mm

**Technical drawing**

