



Product data sheet

Item No. 92.944.0053.1

Male connector with strain relief GST18I4F S2 ZR1 SW

Connector GST18i4, 4 pole, male, spring clamp connection, for cable diameter 9,5 - 11,5 mm, 250V/16A, color of coding: black, colorof housing: black



Item No.	92.944.0053.1
EAN	4015573410596
Order Unit	50 Piece(s)

## Certificates / Approvals



#### Technical data

General	
Rated current	16 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Connection Data

Cable diameter	11.5 mm
Cable diameter 2	9.5 mm
Connection cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.75 mm²
Connection cross section stranded	1.5 mm <sup>2</sup>
Cross section stranded 2	0.75 mm <sup>2</sup>

# 💎 wieland



Terminations per pole	2	
Model		
Model	Plug	
Number of poles	4	
Connection type	Tension clamp connection	
Degree of protection (IP)	IP40	
Remark to type of connection	Finely stranded con. req. Wieland cable end sleeve	

#### Material

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continous temperature	100 °C
Surface finish	Tin-plated

#### Dimensions

Length	75 mm
Width	42.25 mm
Height	17 mm

### Technical drawing

