

Product data sheet

Item No. 92.232.2000.1

Cable assembly GST18I3K1BS 15 20SW

 Extension cable, female - male, length 2m, GST18i3, 3 pole, 250V/16A, cable type H05VV, cross section 1,5 mm², color of coding: black, color of cable: black


Item No.	92.232.2000.1
EAN	4015573319868
Order Unit	40 Piece(s)

Certificates / Approvals

Technical data
General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	
Color of housing inclusive strain relief	Black

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05VV-F
Cable colour	Black
Cable diameter	8.3 mm
Version of cable	Female - male



Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	2 m
--------------	-----

Technical drawing

Farbe colour

Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1 schwarz black	N PE L	L PE N	schwarz black
.2 weiß white	N PE L	L PE N	weiß white
.3 grau grey	N PE L	L PE N	schwarz black
.5 rot red	N PE L	L PE N	schwarz black

Dimensions: 12.6, 28.2, 19.5, 6.9, L ± 3%, 6.9

Labels: Buchsteil/female connector, Steckerteil/male connector

Text: Kabel/cable H05VV-F361,5, Farbe/colour: siehe Tabelle/see table

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST1813K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST1813K1BS 15 X12SW

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Legend: 2005 tag/date, Name, Zeichnung Nr./Drawing No., 92.232.0200.1 01K

Wieland logo

INSTALL COUPLER KONFEKT LEITUNG
Buchse/female - Stecker/male 1,5mm
Cr impulsion/cr impulsion KI 250V

Further data see catalog