

Product data sheet

Item No. 92.238.4000.2

Cable assembly GST18i3K1BS 25 40WS

Extension cable, female - male, length 4m, GST18i3, 3 pole, 250V/16A, cable type H05VV, cross section 2,5 mm², color of coding: white, color of cable: white



Item No.	92.238.4000.2
EAN	4015573361997
Order Unit	15 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	3
Nominal cross section conductor	2.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05VV-F
Cable colour	White
Cable diameter	10.2 mm
Version of cable	Female - male



Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Buchsteil/female connector

Steckersteil/male connector

Gesamtlänge / totale length

Kabel/cable: H05VV-F3G2,5
Farbe/color: siehe Tabelle/see table

.F	Farbe colour	Codierung Buchsteil female	Codierung Steckersteil male	Kabelfarbe cable colour
.1	schwarz black	N R E L	L R E N	schwarz black
.2	weiß white	N R E L	L R E N	weiß white
.3	grau grey	N R E L	L R E N	schwarz black
.5	rot red	N R E L	L R E N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.238.XX00.F	XX in dm-Schritten	92.238.1000.1 = 10dm/L=1000mm	GST1813K1BS 25 10SW
U2.238.XX00.F	XX in m-Schritten	U2.238.1200.1 = 12 m/L=12000mm	GST1813K1BS 25 X12SW

SW = schwarz/black
WS = weiß/white
GR01 = grau/grey
RT03 = rot/red

Typ/type: GST1813K1BS 25

Further data see catalog

INSTALL. COUPLER KONFEKT-LEITUNG
Buchse/Female-Stecker/Female 2,5mm
Cr-impregnation/cr-impregnation K1 250V