

Product data sheet

Item No. 92.232.4000.2

Cable assembly GST18I3K1BS 15 40WS

Extension cable, female - male, length 4m, GST18i3, 3 pole, 250V/16A, cable type H05VV, cross section 1,5 mm², color of coding: white, color of cable: white



Item No.	92.232.4000.2
EAN	4015573330306
Order Unit	25 Piece(s)

Certificates / Approvals



Technical data

General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Model

Number of poles	3
Nominal cross section conductor	1.5 mm ²
Degree of protection (IP)	IP40
Cable type	H05VV-F
Cable colour	White
Cable diameter	8.3 mm
Version of cable	Female - male



Material

Surface finish	Tin-plated
Halogen free	No
Continuous temperature of cable	70 °C
Insulation components continuous temperature	100 °C

Dimensions

Total length	4 m
--------------	-----

Technical drawing

Buchenteil/female connector Steckerteil/male connector

Gesamtlänge / totale length

Kabel/cable H05VV-F361,5
Farbe/colour: siehe Tabelle/see table

.F	Farbe colour	Codierung *X* Buchse female	Codierung *Y* Stecker male	Kabelfarbe cable colour
.1	schwarz black	N PE L	L PE N	schwarz black
.2	weiß white	N PE L	L PE N	weiß white
.3	grau grey	N PE L	L PE N	schwarz black
.5	rot red	N PE L	L PE N	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: schwarz) example (colour: black)	Typ type
92.232.XX00.F	XX in dm-Schritten	92.232.1000.1 = 10dm/L= 1000mm	GST1813K1BS 15 10SW
U2.232.XX00.F	XX in m-Schritten	U2.232.1200.1 = 12 m/L=12000mm	GST1813K1BS 15 X12SW

Typ/type: GST1813K1BS 15 ..
 SW = schwarz/black
 WS = weiß/white
 GR01 = grau/grey
 RT03 = rot/red

2005 Tag/Date Name Zeichnung Nr./Drawing No. Blatt 1 von 1
 T 92.232.0200.1 01K

Wieland
 INSTALL COUPLER
 KONFEKTLEITUNG
 Buchse/female - Stecker/male 1,5mm
 Crimpführung/crimpersion KI 250V

Weitere Daten siehe Katalog
 further data see catalog