



Product data sheet

Item No. 91.931.3053.0

Female connector with strain relief GST15I3S B1 ZR1W WS

Connector GST15i3, 3 pole, female, screw connection, 250V/16A, color of coding: white, color of housing: white



Item No.	91.931.3053.0
EAN	4015573833821
Order Unit	100 Piece(s)

Certificates / Approvals



Technical data

Genera

General	
Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pull relief	Yes
Pollution degree	2
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	White
Marking of poles	
Color of housing inclusive strain relief	White

Connection Data

Cable diameter	9 mm
Cable diameter 2	5.5 mm
Connection cross section solid	1.5 mm ²
Cross section solid 2	0.5 mm ²
Connection cross section stranded	1.5 mm ²
Cross section stranded 2	0.5 mm ²





Terminations per pole	1	
Model		
Model	Bus	
Number of poles	3	
Connection type	Screw connection	
Degree of protection (IP)	IP40	
Material		
Housing material	Polyamide	
Halogen free	Yes	
Contact material	CuZn	
Insulation components continous temperature	100 °C	
Surface finish	Silver-plated	
Dimensions		
Length	53.2 mm	
Width	23 mm	
Height	13.8 mm	

Technical drawing

